



SPECIFICATION FOR SAN MARCO STONE PARTITIONS

Partitions are to be manufactured and installed using the following materials and methods:

PART 1 – MATERIALS

- a. San Marco Stone - Quartz Engineered stone partitions.
- b. Stainless steel door furniture and all fixings.

PART 2 – MANUFACTURE

Partition shall be as follows:

30mm thick double faced San Marco Stone. Both faces of the panels are to be factory polished. Frontal and nib panels are to have both faces of the panel polished and all edges with a 3mm bevel with edge nosings to be factory polished. Panels are available in 3 colours: Snow White, Steel Grey, and Baltic Black.

PART 3 – CLEANING

Immediately following the machine rubbing or fine stoning wash all surfaces with a solution of neutral cleaner, and rinse.

PART 4 – PROTECTION OF FINISHES

When partitions are completely manufactured they shall be protected ready for final site installation.

PART 5 – INSTALLATION

Installation of standard partitions shall be effected in any of the standard methods shown in the list of drawings forming part of this specification and utilizing accessories as described in this specification.

REFER DRWS 001.011B, 002.011B, 003.011B, 004.011B, 005.011B, 006.011B, 008.011B, 011.011A.

PART 6 – DEFINITIONS

Partition

A terrazzo toilet or shower division of specified size, with a standard thickness of 30mm polished on two faces and exposed edges.

Front

A terrazzo front of specified height with standard thickness of 30mm and minimum width of 165mm polished on two faces and exposed edges.

Nib

A terrazzo front of specified height, with standard thickness of 30mm and minimum width of 90mm polished on two faces and exposed edges.

Angle Bracket

A stainless steel angle 50mm x 50mm x 5mm thick and 20mm long, satin finished and complete with 6mm stainless steel Bolts and stainless steel hex nuts.

Channel Capping

A stabilizing channel mounted at the top of partitions 30mm x 16mm internal dimensions. Manufactured from aluminium.

Door Infill

A metal strip fixed to underside of capping, and door openings. Manufactured aluminium.

PART 7 - GUARANTEE

GUARANTEE: The contractor shall furnish a written guarantee against defects due to improper and/or defective materials and/or workmanship for a period of ten years following substantial completion of the partition installation.